

EXCAVATOR MULCHERS

PMM/EX



from 50 to 100 HP



Ø8 cm max



from 6 to 13 t

MULCHER WITH HAMMER/FLAIL ROTOR FOR EXCAVATORS.

The PMM/EX is used for mulching grass and bushes. It is equipped with a variable manual displacement hydraulic piston motor that is designed for cleaning up brambles and shrubs.

The stronger roller supports (optional) ensure the best performance and maximum reliability on difficult terrain. The flow control valve guarantees easy and rapid mounting of the mulcher without adjustments or modifications to the hydraulic system of the excavator.



- Rear roller
- Possibility to have the rotor equipped with PML hammers or Y-flails

- #### OPTIONS
- Customized attachment bracket with pins
 - Attachment plate with self levelling device
 - Stronger bearing for back roller
 - Different teeth

STANDARD EQUIPMENT
Anti dust machine body
Belt transmission
32/65cc variable manual displacement hydraulic piston motor with relief and anticavitation valve
Flow control system valve
Rear hood with mechanical adjustment
Adjustable skids
Welded counter blade



Anti dust machine body

Steel counter-blades helps mulch material into a smaller final size

Stronger bearings for the support roller



Self-cleaning support roller

MODEL	Power (HP)		Flow rate (L/min)		Pressure (bar)		Excavator weight (t.)		Working width (mm)	Weight (kg)	Max shredding diameter (mm)	No. teeth	
	min	max	min	max	min	max	min	max				PMM	Y
PMM/EX 100	50	100	60	130	180	250	6	13	1060	520	80	12	12
PMM/EX 125	50	100	60	130	180	250	6	13	1300	600	80	16	16
PMM/EX 150	50	100	60	130	180	250	6	13	1540	680	80	18	18
PMM/EX 175	50	100	60	130	180	250	7	13	1780	760	80	22	22

Data refers to machine as standard. The technical data in this catalogue may be altered without prior notice.